**DunRite Playgrounds**
www.dunriteplaygrounds.com
sales@dunriteplaygrounds.com

**Telephone:**
(888) 882 - 1929
**Email:**
sales@dunriteplaygrounds.com

# 36 GALLON CLASSIC RECEPTACLE with DOORASH LID LINER $2,544.00

https://www.dunriteplaygrounds.com/store2/74116-36-GALLON-CLASSIC-RECEPTACLE-with-DOORASH-LID-LINER

## Product Image



## Description

The 36 GALLON CLASSIC RECEPTACLE with DOORASH LID LINER, model CL-36AU, is a 36-gallon Classic outdoor waste receptacle with an included ash urn lid and plastic liner. Its hinged service door gives maintenance crews access to the liner without lifting the entire container body. The 2026 manufacturer listing explicitly identifies the ash urn top as the included lid configuration, rather than a separately ordered accessory for this complete SKU.

### Exact model specifications

| | |
|---|---|
| Model | CL-36AU |
| 2026 listed configuration | 36 GALLON CLASSIC RECEPTACLE W/ DOOR, W/ ASH URN LID & PLASTIC LINER |
| Collection | Classic |
| Capacity | 36 gallons |
| Included top | ash urn lid |
| Included liner | Plastic liner |

| | |
|---|---|
| Service access | Hinged access door |
| Finish | Powder-coated welded steel |

## Configuration and companion comparison

| | |
|---|---|
| This version | ash urn lid and plastic liner |
| Other lid configurations | CL-36FT (flat top), CL-36RB (rain bonnet) |
| Liner and lid | Both included in each 2026 CL-36 configuration |
| Mounting | Confirm portable/surface mount requirements with manufacturer |

The Classic receptacle uses welded steel slat construction with a powder-coated finish. The manufacturer drawing describes solid steel hinges and a 36-gallon body measuring approximately 41-1/4 inches high and 28-1/2 inches in diameter. Choose a flat top for a straightforward disposal opening, an ash urn top for the specific designated ash-use configuration, or a rain bonnet where the project calls for that lid design. Do not substitute separate replacement-lid models without confirming fit. Coordinate service clearances around the access door and verify the site attachment method for the installation.